


SPECIFICATION CONTROL DRAWING



D5373-X - OIL DRAIN LINE

DART PART NUMBER	DESCRIPTION	POSSIBLE MANUFACTURER	POSSIBLE MANUFACTURER PART NUMBER	SPECIFICATION	LENGTH "L" (INCHES)	MAX O.D. (INCHES)	MIN I.D. (INCHES)	WEIGHT (LBS)	CONSTRUCTION TYPE	CONSTRUCTION REINFORCEMENT	COVER
D5373-1	OIL DRAIN LINE	STRATOFLEX	101005-4CL-0180	AS4897 SIZE 04 & AS150 TYPE 1AB	18	0.500	0.173	0.26	SEAMLESS, EXTRUDED, CONDUCTIVE POLYTETRAFLUOROETHYLENE	CORROSION-RESISTANT STEEL WIRE BRAID	INTEGRAL SILICONE
			ALT: 101005-4CR-0180								
		AERO-FLEX CORP.	TBD								
D5373-3	OIL DRAIN LINE	STRATOFLEX	101005-4CL-0062		6.25	0.500	0.173	0.17	SEAMLESS, EXTRUDED, CONDUCTIVE POLYTETRAFLUOROETHYLENE	CORROSION-RESISTANT STEEL WIRE BRAID	INTEGRAL SILICONE
			ALT: 101005-4CR-0062								
		AERO-FLEX CORP.	M18000204-0062H								

RELEASED

2021 JUL 23
HB ECR 21-171 47


APPROVED

F	ADD AERO-FLEX AS POSSIBLE MFG (CAR19-290), ADD MFG INDEPENDENT SPECS: AS4897 SIZE CLASS, FITTING THREAD, LOCKWIRE HOLE			PM	19.05.07
E	UPDATED D5373-3/7-9/11, ADDED SHT 3, 4 & 7			WK	17.09.20
D	ADDED D5373-7/9/11			WK	17.04.25
C	ADDED D5373-5			CC	16.12.01
B	ADDED NOTE 8 AND DETAIL A			CC	16.11.07
A	NEW ISSUE			CC	16.01.07
REV.	DESCRIPTION			BY	DATE
DESIGN	CC	DART AEROSPACE USA, INC			
DRAWN	PM	EUGENE, OREGON, USA			
CHECKED	SAD	DRAWING NO.			
MFG. APPR.	SH	REV. F			
APPROVED	VS	D5373			
DE APPR.	DS	SHEET 1 OF 7			
DATE	19.05.07	TITLE			
		SCALE			
		NTS			
		OIL DRAIN LINE			
		COPYRIGHT © 2016 BY DART AEROSPACE USA, INC			
		THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE USA, INC.			

- NOTES:
- 1) MATERIAL: PER TABLE
 - 2) FINISH: NONE
 - 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
 - 4) UNITS: INCHES UNLESS OTHERWISE NOTED
 - 5) BREAK SHARP EDGES: N/A
 - 6) IDENTIFICATION: IDENTIFY WITH DART P/N & B/N USING D2729 LABEL INSTALLED WITH D2182-045 HEAT SHRINK
 - 7) WEIGHT: SEE TABLE
 - 8) FOR PARTS WITHOUT LOCKWIRE HOLE, DRILL LOCK-WIRE HOLES PER SHEET 6, DETAIL A

8 7 6 5 4 3 2 1

SPECIFICATION CONTROL DRAWING



D5373-X - OIL DRAIN LINE

F F F

DART PART NUMBER	DESCRIPTION	POSSIBLE MANUFACTURER	POSSIBLE MANUFACTURER PART NUMBER	SPECIFICATION	LENGTH "L" (INCHES)	MAX O.D. (INCHES)	MIN I.D. (INCHES)	WEIGHT (LBS)	CONSTRUCTION TYPE	CONSTRUCTION REINFORCEMENT	COVER
D5373-5	OIL DRAIN LINE	STRATOFLEX ALT: 101003-4CR-0080 AERO-FLEX CORP.	101003-4CL-0080 AS4897 SIZE 04 & AS150 TYPE 1AB TBD	AS4897 SIZE 04 & AS150 TYPE 1AB	8	0.500	0.173	0.17	SEAMLESS, EXTRUDED, CONDUCTIVE POLYTETRAFLUOROETHYLENE	CORROSION-RESISTANT STEEL WIRE BRAID	INTEGRAL SILICONE

RELEASED


2021 JUL 23

APPROVED

DESIGN	CC	DART AEROSPACE USA, INC.	
DRAWN	PM	EUGENE, OR	
CHECKED	SAD	DRAWING NO.	REV. F
MFG. APPR.	SH	D5373	SHEET 2 OF 7
APPROVED	VS	TITLE	SCALE
DE APPR.	DS	OIL DRAIN LINE	NTS
DATE	19.05.07	COPYRIGHT © 2016 BY DART AEROSPACE USA, INC.	
		THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL, AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE USA, INC.	

- NOTES:
 1) MATERIAL: PER TABLE
 2) FINISH: NONE
 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
 4) UNITS: INCHES UNLESS OTHERWISE NOTED
 5) BREAK SHARP EDGES: N/A
 6) IDENTIFICATION: IDENTIFY WITH DART P/N & B/N USING D2729 LABEL INSTALLED WITH D2182-045 HEAT SHRINK
 7) WEIGHT: SEE TABLE
 8) FOR PARTS WITHOUT LOCKWIRE HOLE, DRILL LOCK-WIRE HOLES PER SHEET 6, DETAIL A

8 7 6 5 4 3 2 1

SPECIFICATION CONTROL DRAWING**D5373-X - OIL DRAIN LINE**

DART PART NUMBER	DESCRIPTION	POSSIBLE MANUFACTURER	POSSIBLE MANUFACTURER PART NUMBER	SPECIFICATION	LENGTH "L" (INCHES)	MAX O.D. (INCHES)	MIN I.D. (INCHES)	WEIGHT (LBS)	CONSTRUCTION TYPE	CONSTRUCTION REINFORCEMENT	COVER
D5373-7	OIL DRAIN LINE	STRATOFLEX	101005-6CL-0150 ALT: 101005-6CR-0150	AS4897 SIZE 06 & AS150 TYPE 1AB	15	0.615	0.298	0.35	SEAMLESS, EXTRUDED, CONDUCTIVE POLYTETRAFLUOROETHYLENE	CORROSION-RESISTANT STEEL WIRE BRAID	INTEGRAL SILICONE

- NOTES:
 1) MATERIAL: PER TABLE
 2) FINISH: NONE
 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
 4) UNITS: INCHES UNLESS OTHERWISE NOTED
 5) BREAK SHARP EDGES: N/A
 6) IDENTIFICATION: IDENTIFY WITH DART P/N & B/N USING D2729 LABEL INSTALLED WITH D2182-045 HEAT SHRINK
 7) WEIGHT: SEE TABLE
 8) FOR PARTS WITHOUT LOCKWIRE HOLE, DRILL LOCK-WIRE HOLES PER SHEET 7, DETAIL D

RELEASED

2021 JUL 23 49

APPROVED

DESIGN	CC	DART AEROSPACE USA, INC	
DRAWN	PM	EUGENE, OREGON, USA	
CHECKED	SAD	DRAWING NO.	REV. F
MFG. APPR.	SH	D5373	SHEET 3 OF 7
APPROVED	VS	TITLE	SCALE
DE APPR.	DS	OIL DRAIN LINE	NTS
DATE	19.05.07	COPYRIGHT © 2016 BY DART AEROSPACE USA, INC	
		THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL, AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE USA, INC.	

8

7

6


5

4

3

2

1

SPECIFICATION CONTROL DRAWING**D5373-X - OIL DRAIN LINE**

DART PART NUMBER	DESCRIPTION	POSSIBLE MANUFACTURER	POSSIBLE MANUFACTURER PART NUMBER	SPECIFICATION	LENGTH "L" (INCHES)	MAX O.D. (INCHES)	MIN I.D. (INCHES)	WEIGHT (LBS)	CONSTRUCTION TYPE	CONSTRUCTION REINFORCEMENT	COVER
D5373-9	OIL DRAIN LINE	STRATOFLEX AERO-FLEX CORP.	101062D0170CL270 ALT: 101062D0170CR270 M130102D0170H270	AS4897 SIZE 06 & AS150 TYPE 1AB	17	0.615	0.298	0.41	SEAMLESS, EXTRUDED, CONDUCTIVE POLYTETRAFLUOROETHYLENE	CORROSION-RESISTANT STEEL WIRE BRAID	INTEGRAL SILICONE


- NOTES:
- 1) MATERIAL: PER TABLE
 - 2) FINISH: NONE
 - 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
 - 4) UNITS: INCHES UNLESS OTHERWISE NOTED
 - 5) BREAK SHARP EDGES: N/A
 - 6) IDENTIFICATION: IDENTIFY WITH DART P/N & B/N USING D2729 LABEL INSTALLED WITH D2182-045 HEAT SHRINK
 - 7) WEIGHT: SEE TABLE
 - 8) FOR PARTS WITHOUT LOCKWIRE HOLE, DRILL LOCK-WIRE HOLES PER SHEET 7, DETAIL D

RELEASED2021 JUL 23 *mf***APPROVED**

DESIGN	CC	DART AEROSPACE USA, INC.	
DRAWN	PM	EUGENE, OR	
CHECKED	SAD	DRAWING NO.	REV. F
MFG. APPR.	SH	D5373	SHEET 4 OF 7
APPROVED	VS	TITLE	SCALE
DE APPR.	DS	OIL DRAIN LINE	NTS
DATE	19.05.07	COPYRIGHT © 2016 BY DART AEROSPACE USA, INC. THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE USA, INC.	

8 7 6 5 4 3 2 1

SPECIFICATION CONTROL DRAWING



D5373-X - OIL DRAIN LINE

DART PART NUMBER	DESCRIPTION	POSSIBLE MANUFACTURER	POSSIBLE MANUFACTURER PART NUMBER	SPECIFICATION	LENGTH "L" (INCHES)	MAX O.D. (INCHES)	MIN I.D. (INCHES)	WEIGHT (LBS)	CONSTRUCTION TYPE	CONSTRUCTION REINFORCEMENT	COVER
D5373-11	OIL DRAIN LINE	STRATOFLEX	101062B0160CL270	AS4897 SIZE 04 & AS150 TYPE 1AB	16	0.500	0.173	0.26	SEAMLESS, EXTRUDED, CONDUCTIVE POLYTETRAFLUOROETHYLENE	CORROSION-RESISTANT STEEL WIRE BRAID	INTEGRAL SILICONE
			ALT: 10162B0160CR270								
		AERO-FLEX CORP.	M180102B0160H270								


RELEASED

2021 JUL 23 *11*

APPROVED


DESIGN	CC	DART AEROSPACE USA, INC.			
DRAWN	PM	EUGENE, OR			
CHECKED	SAD	DRAWING NO.			
MFG. APPR.	SH	REV. F			
APPROVED	VS	D5373			
DE APPR.	DS	SHEET 5 OF 7			
DATE 19.05.07		TITLE			
F		SCALE			
NOTES:		NTS			
1) MATERIAL: PER TABLE 2) FINISH: NONE 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED 4) UNITS: INCHES UNLESS OTHERWISE NOTED 5) BREAK SHARP EDGES: N/A 6) IDENTIFICATION: IDENTIFY WITH DART P/N & B/N USING D2729 LABEL INSTALLED WITH D2182-045 HEAT SHRINK 7) WEIGHT: SEE TABLE 8) FOR PARTS WITHOUT LOCKWIRE HOLE, DRILL LOCK-WIRE HOLES PER SHEET 6, DETAIL A					
<small>COPYRIGHT © 2016 BY DART AEROSPACE USA, INC. THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE USA, INC.</small>					

8 7 6 5 4 3 2 1



8 7 6 5 4 3 2 1

8 7 6 5 4 3 2 1



8 7 6 5 4 3 2 1